

ALUMINUM INDOOR COILS

J4MXC | J4GXC



- ▶ All aluminum coil design.
- ▶ Models available: 1.5 – 5 ton
- ▶ 16 different models are available to suit a variety of situations and budgets.
- ▶ J4MXC Oxbox cased coils may be installed in upflow, downflow or horizontal applications to fit the space provided in your customer's home.
- ▶ J4GXC Oxbox cased coils are upflow and downflow only.
- ▶ Foil-faced thermal insulation makes cleaning simple and helps reduce service time.
- ▶ **Factory-installed fixed metering device (piston) (Flow Control Check Valve - FCCV)**

OXBOX™

A TRANE® BRAND

The Oxbox line of heating and cooling products offer you flexible and affordable options for your HVAC equipment needs. The function of indoor air coils is simple: heating or cooling your system's air and removing humidity. Oxbox indoor air coils make that process as effective as possible, maximizing the efficiency of all system components—and keeping you as comfortable as possible in all seasons.

J4MXC COIL Upflow/Downflow and Horizontal Left/Right

Model #	Tonnage	Height (in.)	Width (in.)	Depth (in.)
J4MXCA003EC6HC*	1.5 - 3.0	20	14.5	21
J4MXCB004EC6HC*	1.5 - 3.0	20	17.5	21
J4MXCC005EC6HC*	1.5 - 3.0	20	21	21
J4MXCC009EC6HC*	3.0 - 5.0	30	21	21
J4MXCD010EC6HC*	3.5 - 5.0	30	24.5	21
J4MXCB016EC6HC*	2.5 - 3.5	30	17.5	21
J4MXCC017EC6HC*	2.5 - 4.0	30	21	21
J4MXCD018EC6HC*	3.0 - 4.0	30	24.5	21

*Indicates a minor design sequence change.

Note: All coils are shipped with a Fixed Metering Device (Flow Control Check Valve - FCCV). Some rated combinations require a TXV kit, ordered separately. See the coil Installation Instructions for piston and TXV matches.

SEE PAGE 2 FOR J4GXC COIL SPECIFICATIONS



ALUMINUM INDOOR COILS

J4MXC | J4GXC

OXBOX[™]
A TRANE® BRAND



J4GXC COIL Upflow and Downflow

Model #	Tonnage	Height (in.)	Width (in.)	Depth (in.)
J4GXCA003EC6HU*	1.5 - 3.0	20	14.5	21
J4GXCB004EC6HU*	1.5 - 3.0	20	17.5	21
J4GXCC005EC6HU*	1.5 - 3.0	20	21	21
J4GXCC009EC6HU*	3.0 - 5.0	30	21	21
J4GXCD010EC6HU*	3.5 - 5.0	30	24.5	21
J4GXCB016EC6HU*	2.5 - 3.5	30	17.5	21
J4GXCC017EC6HU*	2.5 - 4.0	30	21	21
J4GXCD018EC6HU*	3.0 - 4.0	30	24.5	21

*Indicates a minor design sequence change.

Note: All coils are shipped with a Fixed Metering Device (Flow Control Check Valve - FCCV). Some rated combinations require a TXV kit, ordered separately. See the coil Installation Instructions for piston and TXV matches.



WARRANTIES AVAILABLE:

- ❑ 1 year unit replacement.*
- ❑ 10 year warranty on parts with product registration.
- ❑ 10 year compressor replacement.
- ❑ Warranty stays with the home.

Base warranty is still available without registration.

*If the compressor, coil or heat exchanger fails in the first year.



Our enhanced warranty gives you maximum peace of mind. Plus, every piece of equipment is warranted to the home, not the homeowner — providing an extra measure of coverage when it comes time to sell.

Questions? Go to [OXBOXHVAC.COM](https://www.oxboxhvac.com) for more information.

