

GAS FURNACES

80% | 96%



When the weather gets chilly, you'll get comfortable, consistent heating—and you can also be confident these furnaces are built for durable performance over the long haul.



80% Single Stage Upflow/Downflow/Horizontal Right/Left

Model #	AFUE	BTU Input	Airflow Direction	Dimensions (in.) (H x W x D)
J801V040AM3SEA	80%	40,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 14.5 x 28.5
J801V060AM3SEA	80%	60,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 14.5 x 28.5
J801V060BM4SEA	80%	60,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 17.5 x 28.5
J801V080BM4SEA	80%	80,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 17.5 x 28.5
J801V080CM4SEA	80%	80,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 21.0 x 28.5
J801V100CM5SEA	80%	100,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 21.0 x 28.5
J801V120DM5SEA	80%	120,000	Upflow/Downflow/Horizontal Right/Left	33.7 x 24.5 x 28.5

96% Dual Stage Upflow/Horizontal Right/Left

Model #	AFUE	BTU Input	Airflow Direction	Dimensions (in.) (H x W x D)
J962X060BU3SEA	96%	60,000	Upflow/Horizontal Right/Left	33.7 x 17.5 x 28.8
J962X080BU3SEA	96%	80,000	Upflow/Horizontal Right/Left	33.7 x 17.5 x 28.8
J962X080CU4SEA	96%	80,000	Upflow/Horizontal Right/Left	33.7 x 21.0 x 28.8
J962X100CU5SEA	96%	100,000	Upflow/Horizontal Right/Left	33.7 x 21.0 x 28.8
J962X100DU5SEA	96%	100,000	Upflow/Horizontal Right/Left	33.7 x 24.5 x 28.8
J962X120DU5SEA	96%	120,000	Upflow/Horizontal Right/Left	33.7 x 24.5 x 28.8

J801V and J962X Accessories

Part Number	Description
JAYHAKFURN962XA	High Altitude Kit, 96% Furnace
JAYHAKFURN801VXA	High Altitude Kit, 80% Furnace

Our innovative 1-5-10 no-registration warranty gives you maximum peace of mind. Plus, every piece of equipment is warranted to the home, not the homeowner—providing an extra measure of coverage when it comes time to sell.

WARRANTIES AVAILABLE:

- ▶ **1 Year: Complete Replacement**
Only compressors, coils, or heat exchanger failure
- ▶ **5 Years: Standard Parts Warranty**
- ▶ **10 Years: Compressor Replacement**

Questions? Go to OXBOXHVAC.COM for more information.

- ▶ Furnace models feature aluminized steel heat exchangers to conduct heat quickly and increase durability
- ▶ Oxbox furnaces are designed for multi-position installation allowing for easy replacement or new construction installations
- ▶ Twinning capability built in. No kit required
- ▶ Furnaces are fully convertible to either natural gas or propane, making them suitable for use in any area - LP kit included
- ▶ Painting galvanized steel cabinet that passed 500 hour salt spray test
- ▶ Quiet, multi-speed ECM circulator blower motor
- ▶ FER compliant

For installation in SCAQMD only: These J962X furnaces do not meet the SCAQMD Rule 1111 14 ng/J NOx emission limit and are only eligible for installation in high altitude (4,200 feet and above) or propane applications and are subject to a mitigation fee of up to \$450 USD. These furnaces are not eligible for the Clean Air Furnace Rebate Program: www.CleanAirFurnaceRebate.com.

The J801V NOx emission level is >40 ng/J and can't be sold and/or installed where State and/or District regulations require <40 ng/J.