




TAG: _____

SUBMITTAL

2.0 Ton Heat Pump Package Units J4PH4024A1000AA



PRODUCT SPECIFICATIONS

Specifications

MODEL	J4PH4024A1000AA
POWER CONNS. - V/PH/HZ	208/230/1/60
MIN. BRCH. CIR. AMPACITY	13.7
BR. CIR. PROT. RTG. - MAX. (AMPS)	20
SOUND POWER LEVEL [dB(A)]	72
COMPRESSOR	ROTARY
NO. USED- NO. SPEEDS	1-1
VOLTS/PH/HZ	208/230/1/60
R.L. AMPS- L.R. AMPS	8.45 - 34.8
FACTORY INSTALLED	
START COMPONENTS	NO
INSULATION/SOUND BLANKET	NO
COMPRESSOR HEAT	NO
OUTDOOR FAN	
DIA. (IN.)	22
TYPE DRIVE- NO. SPEEDS	DIRECT - 1
MOTOR HP	1/12
MOTOR SPEED R.P.M.	1075
VOLTS/PH/HZ	208/230/1/60
F.L. AMPS	0.68
OUTDOOR COIL- TYPE	PLATE FIN
ROWS- F.P.I.	2.5 - 20
FACE AREA (SQ. FT.)	9.79
TUBE SIZE (IN.)	9/32

INDOOR FAN- TYPE	Centrifugal
DRIVE- NO. SPEEDS	DIRECT - 3
CFM VS. IN. WG.	See Fan Performance Table
MOTOR HP	1/4
MOTOR SPEED R.P.M.	1075
VOLTS/PH/HZ	208/230/1/60
F.L. AMPS	2.46
INDOOR COIL- TYPE	PLATE FIN
ROWS- F.P.I.	4 - 17
FACE AREA (SQ. FT.)	3.63
TUBE SIZE (IN.)	9/32
REFRIGERANT CONTROL	ORIFICE
REFRIGERANT	
LBS. - R-410 (O.D. UNIT)	5 LBS. - 1 OZ.
DIMENSIONS	W X H X D
CRATED (IN.)	52-3/8X25-7/8X38-5/8
WEIGHT	
SHIPPING (LBS.)	333
NET (LBS.)	326

Optional Heater

Heater Kit Model Used	Electric Heat (kW)	Min. Circuit Ampacity		Max. Fuse or Breaker (HACR) Ampacity	
		208V	240V	208V	240V
JAYHTR1P05BKRA	5	23	26	25	30
JAYHTR1P08BKRA	7.5	34	39	35	40
JAYHTR1P10BKRA	10	45	52	45	60

Fan Performance Table

Motor Speed	AIR FLOW PERFORMANCE								
	J4PH4024A1000AA								
	External Static Pressure-Inches W.C. (kPa)								
		0(0)	0.1(.02)	0.2(.05)	0.3(.07)	0.4(.10)	0.5(.12)	0.6(.15)	0.7(.17)
Low	CFM	756	706	654	600	-	-	-	-
Medium	CFM	-	-	-	842	782	718	625	-
High	CFM	-	-	-	-	-	889	805	693

Features

- 2-5 ton capacities available
- High-efficiency 14 SEER ratings
- Architectural, anti-rust steel cabinets, tested to withstand 1,000-hour salt spray
- Quiet horizontal discharge
- High-efficiency compressors operate smoothly, quietly, consistently
- Auxiliary electric heaters available as a field installed option: 5kW,8kW,10kW,15kW,20kW (available heater sizes vary depending on model tonnage)
- Suitable for Manufactured/Mobile Home Use



The manufacturer has a policy of continuous product and product data improvement and it reserves the right to change design and specification without notice.

BX-PRQ-J4PH4024A1000A-1A